# Scotch<sup>TM</sup> Brand No. 390 Polyethylene Coated Cloth Tape

January 1995

**DESCRIPTION:** A polyethylene coated cloth tape designed for applications

requiring some strength and moisture resistance.

#### **CONSTRUCTION:**

Backing: Polyethylene coated cloth

Adhesive: Rubber

Color: Olive green, Silver Standard Roll Length: 60 yds (55 m)

TYPICAL PHYSICAL PROPERTIES: Note: The following technical information and data

should be considered representative or typical only, and should not be used for specification purposes.

# **ASTM TEST METHOD**

Adhesion to Steel: 73 oz./in. width (80 N/100 mm) D-3330
Tensile Strength at Break: 50 lb s./in. width (876 N/100 mm) D-3759
Elongation at Break: 12% D-3759
Total Tape Thickness: 12 mils (.30 mm) D-3652

# **GENERAL INFORMATION:**

- 1. The high tack, conformability and strength, and easy tear features of this tape lend itself to many sealing and general purpose applications.
- 2. Typically used at room temperature but will function up to 200 °F (93°C) for up to 1 hour.

### SHELF LIFE:

To obtain best performance, use this product within one year from date of manufacture and store under normal conditions of 70 °F (21°C) and 50% R.H. in the original carton.

#### **POSSIBLE USES:**

Sealing, waterproofing, and protecting articles for shipment where moisture proofing is important, such as overseas shipments

The silver colored tape is used in the construction industry for duct sealing and holding of insulation materials.

Scotch<sup>™</sup> Brand No. 390 Polyethylene Coated Cloth Tape Page 2

<u>FEATURES</u>	<u>ADVANTAGES</u>	<u>BENEFITS</u>
Treated cloth	Resists moisture	Prolongs tape bond
	Conformable	
	Hand tears easily	Ease of application
	Good tensile strength	
Rubber resin adhesive	High tack	Provides good seal
	Good holding power	Reduces material damages

Technical Data: All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. 3M recommends each user determine the suitability of the tape for the intended use.

Warranty and Limited Remedy: THE FOLLOWING WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, A CUSTOM OR USAGE OF TRADE:

3M warrants its tapes will be free from all defects in materials and manufacture. If tape is proved to be defective, then the exclusive remedy and 3M's and seller's sole obligation shall be, at 3M's option, to replace the quantity of the product which is proved to be defective or to refund the purchase price.

Limitation of Liability: 3M and seller shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability or any other legal theory.

The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by a written agreement signed by authorized officers of 3M and seller.